(19) Europäisches Patentamt
European Patent Office
Office européen des brevets

(11) Publication number: **0 204 094**
**A2**

# (12) EUROPEAN PATENT APPLICATION

(21) Application number: 86104403.0

(22) Date of filing: 01.04.86

(51) Int. Cl.4: H04N 1/40 , H04N 1/46

(30) Priority: 30.03.85 JP 64966/85
23.08.85 JP 184274/85

(43) Date of publication of application:
10.12.86 Bulletin 86/50

(84) Designated Contracting States:
DE GB IT NL

(71) Applicant: HITACHI, LTD.
6, Kanda Surugadai 4-chome Chiyoda-ku
Tokyo 100(JP)

(72) Inventor: Kobayashi, Shin'ya
2467 Motoyoshidacho
Mito-shi(JP)
Inventor: Anzai, Masayasu
20-8 Kanesawacho 5-chome
Hitachi-shi(JP)

(74) Representative: Strehl, Schübel-Hopf, Groening, Schulz
Widenmayerstrasse 17 Postfach 22 03 45
D-8000 München 22(DE)

## (54) Scanning recording type printing method and apparatus for realizing the same.

(57) A scanning recording type printing method, by which a pixel recroding pulse signal (S) is produced by comparing a comparison data signal (DB), which is formed by repeating an up counting operation and a down counting operation for every pixel, which is the smallest unit region of an image, with a depth data signal (DA) for one scanning line and the location of each of net points of at least one color printed within a pixel is controlled by the pixel recording pulse signal (S) so that worsening of the image quality in a high precision fine image printing can be reduced.

FIG. 1




EP 0 204 094 A2

# SCANNING RECORDING TYPE PRINTING METHOD AND APPARATUS FOR REALISING THE SAME

## BACKGROUND OF THE INVENTION

This invention relates to a monochrome or color printing method and an apparatus for realizing the same and in particular to a scanning recording type printing method and an apparatus for realizing the same permitting to reduce worsening of the image quality in a high precision fine image recording.

As a method for varying the recording area of each pixel in order to express light and shade of the image in a scanning recording type printing apparatus, there is known a method, by which image recording pulse signals are modulated in pulse width by means of data representing the depth. Apparatuses described in Japanese Patent Application un-examined publications Nos. 82-57679 and 82-99866 are its concrete examples.

In such a printing recording apparatus it is necessary to reduce each cell in size and increase the pixel density in order to be able to record an image with a high precision and a high fineness. The scanning direction and the size of each pixel in the scanning recording are determined by the scanning speed and the production period of the image recording pulse signal. Consequently, in order to make each pixel smaller, the production period of the image recording pulse signal must be shortened and the rate of the intermission must be increased. However, when the rate of the intermission of the image recording pulse signal is increased. The image quality has a tendence to be lowered.

The reason will be explained concretely taking an electro-graphic laser beam printer as an example.

In Fig. 2, a memory device 1 stores depth data of each of the pixels in image signals coming from an image read-out device or a computer (not shown in the figure) for one scanning line. The depth data are sent to a latch 2 in the form of pixel depth data DA for every pixel, depending on the position of recording scanning by a pixel clock signal PCLK1 given by a timing treatment circuit 4, which will be described later. Supposing that the pixel depth is represented by 16 degrees from "0" (white) to "15" (black), the pixel depth data DA are 4 bit data. In a pixel recording pulse signal generation circuit 9 the latch 2 holds (latches) the pixel depth data DA by a pixel clock signal PCLK2 given by the timing treatment circuit 4 and its holding period of time is equal to a period of time during which one pixel domain is scanned for recording. These pixel depth data DA held by the latch 2 are given to a comparator 5. A counter 3 which is a cyclic 4 bit binary counter, counts clock signals CLK1 coming from a clock generator 10 under the control by a recording scanning signal LINE1 from the timing treatment circuit 4. 16 clock signals CLK1 are outputted for a period of time during which one pixel domain is scanned for recording. The counter 3 counts up from "0" (white) to "15" (black) and gives the content of the count as comparison data DB to the comparator 5. At the same time, it gives a carry signal as pixel clock signal PCLK3 to the timing treatment circuit 4. The timing treatment circuit 4 generates the pixel clock signals PCLK1 and PCLK2, referring to the pixel clock signal PCLK3 and at the same time uses a detection signal LINE2 coming from a laser beam detector 8 as a recording scanning start synchronization signal for every scanning line.

The comparator 5 compares the pixel depth data DA with the comparison data DB and generates a 2-value pixel recording pulse signal S, corresponding to

"black , if DA > DB

"white , if DA ≤ DB,

which is given to a semiconductor laser circuit 6. A laser beam outputted by the semiconductor laser circuit 6 is deflected in a region of an angle $\theta$ so as to scan and illuminate an electro-graphic photosensitive drum 7. In this way an electro-static latent image is formed thereon and transferred to a recording paper, after having being developed with toner. After that, it is further fixed so as to be a record.

Figs. 1(A) to 1(C) indicates a timing chart representing the working mode of the pixel recording pulse signal and the pixel recording in such a laser beam printer. (A) indicates the pixel number and the pixel depth data DA. The abscissa t in (B) represents the time, in which T denotes the period of time necessary for scanning to record one pixel. The coordinate represents digital values corresponding to pixel depths, in which "0" indicates "white"; "15" indicates "black"; DA shows the pixel depth data; and DB shows the comparison data. The abscissa x in (C) represents the position of the recording scanning of the laser beam and hatched regions show the recorded area for each of the pixels.

In such a recording method, since the laser beam outputted by the semiconductor laser circuit 6 has a certain spread in the scanning direction, when this laser beam is interrupted by the pixel recording pulse signal S in the course of the scan-

ning, the light quantity at both the border portions of the recorded dots in the main scanning direction on the pixel recording surface is inconveniently in an intermediate region between white and black and thus the depth of the record at these portions is unstable, what is a factor lowering the image quality. This is produced by the fact that the laser beam has a certain spread. Consequently, when, in order to record finer image with a high precision, pixels are made smaller and the number of interruptions of the laser beam is increased, the proportion of such unstable regions increases, what gives rise to lowering the image quality.

Such phenomena are not limited to the laser beam printer, but produced in common in photosensitive recording apparatuses, in which recording energy given to recording medium is interrupted and controlled in the course of scanning, stylus electro-static recording apparatuses, and scanning recording type recording apparatuses such as scanning illumination type electro-graphic printers using liquid crystal light switches and light emitting diodes.

On the other hand, in the color printing by offset printing, it is difficult to position net points (i.e. dots) to be printed with a high precision. For example, in the case of a multi-block printing with 4 blocks of cyan, yellow, magenta and Indian ink, when it is tried to superpose corresponding dots of different blocks on each other, slight misalignment produces Moireé fringes (interference fringes). Therefore, in practice, the screen angles of net points of different blocks are intentionally varied appreciably so that the net points of different colors are superposed at random, in order to prevent the production of low frequency Moireé fringes. However, by this method, superposition of dots of different colors is irregular, what prevents to effect theoretical color correction.

To the contrary, in a digital printer such as a laser beam printer, etc, since it is possible to position fairly precisely dots, even when it is tried to superpose corresponding dots of different blocks on each other, there are produced no Moireé fringes.

An article by SAYANAGI published in Denshi-Shashin Gakkaishi (Journal of the Electro-Graphic Society) 23, No. 3 (1984) (in Japanese) has disclosed a "concentric solution model", by which the dots are printed by a digital printer so that their centers are superposed on each other (cf. Fig.(3A)) and reported that 100% under color removal (UCR) is possible by this method (cf. Fig. 3(B). If this concentric solution model could be realized ideally, a perfect UCR (100% UCR) and other various color correction theories would be efficacious. However, this concentric solution model has not taken the following points into consideration.

1) Although the dots formed by printing are, in general, ideally printed at the central portion, but they are not precisely printed at the peripheral portion because of scattering of inks or unevenness of printing. According to the concentric solution model, since the net points other than the dot of the ink, which is at the top, exhibit their color by their peripheral portion, it is difficult to reproduce the precise color.

2) When the UCR is effected according to the concentric soldtion model, since a block net point (dot) by an Indian ink block is at the top, other inks printed under the black net point come to nothing and in addition, the net point (dot) is apt to be transferred imperfectly because of the superposition of useless inks.

3) Even by a digital printer, the net points of different colors deviate more or less from each other because of expansion or contraction of paper, etc. The concentric solution model is poor at this position divergence and the risk that Moireé fringes are produced is high.

## SUMMARY OF THE INVENTION

The object of this invention is to provide a scanning recording type printing method and an apparatus for realizing the same permitting to reduce worsening of the image quality in the high precision fine image recording by controlling the location of net points of at least one color printed within a pixel.

According to this invention, in a scanning recording type print recording apparatus, in which depth data of each of the pixels in the image signal are transformed into an image recording pulse signal having a time width proportional to the depth for each of the pixels and production of recording energy is controlled so as to be interrupted by this image recording pulse signal, worsening of the image quality is reduced by reducing the proportion of the area of unstable regions. That is, this invention is characterized in that, by producing the rear end of the recording pulse signal of the preceding recording side pixel in a pair of pixels adjacent to an arbitrarily selected pixel in the recording scanning direction in accordance with the rear end of the relevant pixel and the front end of the recording pulse signal of the succeeding recording side pixel in accordance with the front end of the relevant pixel so that the production of the recording energy between this pair of pixels is continuous and by making the region, where the recording depth is unstable, smaller, worsening of the image quality is reduced.

On the other hand, the "pixel" is the smallest unit of spatial resolving power, when an original analogue image is quantized (digitalized) and in general it is defined so as to be sufficiently small. In a digital printer, however many net points are formed in this pixel and wherever the net points are written in this pixel, no differences therebetween cannot be recognized by human eye. In other words, within a pixel, wherever the net points are moved, the movement itself doesn't lower the resolving power. For example, in the case where a pixel is large, the Bayer method is adopted, by which one pixel is represented by many small net points (dots), or a net point is formed at a position deviated from the center of the pixel in order to have a screen angle. Also according to this invention attention is paid to this point and in full color printing by multi-block printing, the net points (dots) of each of the colors formed within one pixel are not concentrated to one point, which is the center of the pixel, contrarily to those in the concentric solution model, but they are suitably arranged within the pixel for every color. In this way superposition of the net points of different colors can be controlled and as the result a high quality full color printing can be effected.

That is, this invention is characterized in that, when an intermediate chrominance is printed by effecting area-modulation depending on a plurality of colored inks within a pixel, which is the smallest unit region of spatially quantized image data, an area-modulation is effected by arranging a first colored ink of at least one color at a first position within the pertinent pixel and another area-modulation is effected by arranging a second colored ink of at least one color, which is different from the first colored ink, at a second position within the pertinent pixel, which is different from the first position.

In a preferred embodiment according to this invention, the first colored ink mentioned above is arranged from one end within the pixel towards the center of the pixel and the second colored ink mentioned above is arranged from another end within the pixel towards the center of the pixel.

In another preferred embodiment according to this invention, the one end and the another end stated above are one end and the other end in the main scanning direction within the pixel.

In still another preferred embodiment according to this invention, the first colored ink stated above is constituted by a multi-layer structure consisting of yellow ink, magenta ink and cyan ink and the second colored ink stated above is constituted by black ink.

In still another preferred embodiment according to this invention, in an arbitrarily selected pixel the first colored ink mentioned above is arranged from one end within the pixel towards the center of the pixel and the second colored ink mentioned above is arranged from another end within the pixel towards the center of the pixel, and further in pixels adjacent to the arbitrarily selected pixel mentioned above the first colored ink is arranged from the another end within the pixel towards the center of the pixel and the second colored ink is arranged from the one end with the pixel towards the center of the pixel.

## BRIEF DESCRIPTION OF THE DRAWINGS

Figs. 1 (A) -(G) represent a timing chart for explaining the working mode; (A) indicating pixel numbers and pixel depth data; (B) and (C) the working mode for production of the pixel recording pulse signal and the pixel recording pattern according to prior art techniques; (D) -(G) the working mode for production of the pixel recording pulse signal and the pixel recording pattern by the method according to this invention;

Fig. 2 is a block diagram illustrating the construction of a prior art laser beam printer;

Figs. 3 (C) and (D) are schemes for explaining the principle of this invention in color printing, and Figs. 3 (A) and (B) are corresponding schemes for explaining the prior art techniques;

Fig. 4 is a block diagram indicating a comparison data production circuit for realizing this invention;

Figs. 5 (H) -(P) are schemes for explaining the working mode for production of the pixel recording pulse signal and the pixel recording pattern by means of the circuit indicated in Fig. 4;

Fig. 6 shows graphs indicating more in detail the embodiment of this invention indicated in Fig. 3 (D);

Fig. 7 is a block diagram indicating a circuit for obtaining the pixel recording pattern according to an embodiment of this invention;

Fig. 8 shows graphs for explaining the working mode of the circuit indicated in Fig. 7;

Figs. 9 -11 show embodiments in the case where the position of dots is controlled not only in the main scanning direction but also in the auxiliary scanning direction, indicating the position of dots, information given to the printer and the dot pattern recorded by printing, respectively;

Fig. 12 is a block diagram indicating the construction of a circuit, which is another embodiment of this invention;

Fig. 13 is a block diagram indicating the construction of a circuit, which is still another embodiment of this invention; and

Fig. 14 is a scheme for explaining the principle of the circuit indicated in Fig. 13.

DESCRIPTION OF THE PREFERRED EMBODIMENTS

Figs. 1 (D), (E) and (F), (G) are timing chart illustrating the working mode of the production of the pixel recording pulse signal and the pixel recording according to this invention.

(D) shows the working mode of the production of the pixel recording pulse signal using the comparison between pixel depth data DA and comparison data DB in which the magnitude of the comparison data DB varies so that it increases in the odd pixel number regions and decreases in the even pixel number regions. In this way, the position of production of the pixel recording pulse signal S generated by comparing the pixel depth data DA with the comparison data is so determined that in the odd pixel number regions the front end of the pixel recording pulse signal is in accordance with the front end of the pertinent pixel and in the even pixel number regions the rear end of the pixel recording pulse signal S is in accordance with the rear end of the pertinent pixel, i.e. the rear end of the recorded dot in the main scanning direction and thus in the example indicated in the figure the pixels No. 2 and No. 3, and No. 4 and No. 5 become continuous. Consequently, in the recording pixels recorded on the basis of this pixel recording pulse signal, as indicated in (E), the pixels No. 2 and No. 3, and No. 4 and No. 5 are continuous, respectively, and thus there are no border portions in the scanning direction between the pixels belonging to each of the pairs. Therefore the unstable region becomes smaller.

(F) shows an example, where the magnitude of the comparison data DB decreases in the odd pixel number regions and increases in the even pixel number regions. In the recording pixels of this case, as indicated in (G), the pixels No. 1 and No. 2, and No. 3 and No. 4 are continuous.

Now, the pixel recording pulse signal production circuit used for such a pixel recording will be explained. The production of the pixel recording pulse signal by the comparison between the pixel depth data DA and the comparison data DB, as previously indicated in Fig. 1(D) can be effected by ameliorating the circuit generating the comparison data DB indicated in Fig. 2. Therefore, here this circuit generating the comparison data DB will be explained and explanation of the other circuits will be omitted, because they are identical to those used in prior art apparatuses. Further each of output terminals of each of the circuits and the signal produced there are denoted with a same reference numeral.

In Fig. 4, a counter 13 is a hexadecimal counter, which counts clock signals CLK1 inputted from a clock generator 10 to its clock terminal CLK. The recording scanning signal LINE1 outputted by the timing treatment circuit 4 is at the high level during the recording scanning. The counter 13 stated above counts the clock signals CLK1, when this recording scanning signal LINE1 inputted to the clear terminal CLR is at the high level and it is cleared to "0", when the signal LINE1 is at the low level. The output signal $Q_{13}$ of the counter 13 is inputted as it is to an input terminal A of a data selector 14 and the reversed value of the output signal $Q_{13}$ is inputted to another input terminal B thereof. That is, when the output signal $Q_{13}$ of the counter 13, "0" is inputted to the input terminal A and "15" to the input terminal B. This data selector 14 outputs the input signal selectively at one of the input terminals A and B stated above, depending on the signal level inputted to its selection control terminal Sel. To this selection control terminal Sel is given the output signal $Q_{12}$ of an RS flip-flop - (hereinbelow abbreviated to FF) 12. A latch 15 outputs the signal inputted to its input terminal D as it is from its output terminal as the output signal ($Q_{15}$ (comparison data DB) and effects data latch, depending on the signal level of the pixel clock signal given to its enable terminal En. Further the carry signal outputted to the carry terminal Car of the counter 13 stated above is reversed to become the pixel clock signal PCLK3, which is supplied to the timing treatment circuit 4, to the clock terminal CLK of FF 12 and to the enable terminal En of the latch 15.

In the construction of the circuit described above, when the recording scanning signal LINE1 outputted from the timing treatment circuit 4 is at the high level, the counter 13 counts the clock signals CLK1 given by the clock generator 10 and increases the value of the counting output signal $Q_{13}$. When the value of the counting output signal $Q_{13}$ reaches "15", a carry signal is produced at the carry terminal Car. When the data selector 14 is set at the initial state so that the signal at the input terminal A is selected to be outputted, the comparison data DB, which are the output signal $Q_{15}$ of the latch 15 increases successively from "0" to "15". When the value of the count reaches "15" and a carry signal Car is outputted, the latter is given to the enable terminal En of the latch 15 as the pixel clock signal PCLK3 and the latch 15 stated above latches "15". Since the pixel clock signal PCLK3 is given also to the FF 12, the FF 12 is inverted and the signal level of its output signal $Q_{12}$ is changed. By this change of the signal level of the output signal $Q_{12}$ the data selector 14 selects the signal at the input signal B and outputs a signal at its output terminal Y. Consequently the value at the output

terminal Y of the data selector 14 varies from "15" to "0", but since the latch 15 latches "15", the comparison data DB remains to be "15". The above is the signal treatment for the pixel of pixel number 1. When the succeeding clock signal CLK1 is inputted, the content of the counter 13 becomes "0". Consequently the value at the output terminal Y of the data selector 14 becomes "15" and the signal treatment proceeds to the treatment for the pixel of pixel number 2. At the same time the carry signal Car of the counter 13 disappaars and therefore the latch 15 outputs the signal at the input terminal D as it is. After that the counter 13 counts the clock signals CLK1 and its content increases. However, since the data selector 14 outputs the value at the terminal B, to which the reversed signal is inputted, the comparison data DB, which is the output signal $Q_{15}$ of the latch 15, decreases successively. When the content of the counter 13 reaches "15" (comparison data DB = 0), a carry signal Car is outputted and thus the latch 15, the FF 12 and the data selector 14 are controlled in the same way as stated above. At this time the data selector 14 is so commuted that the signal at the input terminal A is selected and outputted at the output terminal Y.

The comparison data DB repeats its increase and decrease, as indicated in Fig. 1(D), by the fact that such operations are repeated in a period of time, during which the recording scanning signal LINE1 is at the high level.

Such a comparison data production circuit has an advantage that a high speed operation is possible with respect to the case where the counter 13 counts up and down.

Then it is possible to obtain the pixel recording pulse signal for effecting the pixel recording, as indicated in Fig. 1(E), while comparing the magnitude of the comparison data DB thus obtained with that of the pixel depth data DA.

In addition, when the output signal $Q_{12}$ of the FF 12 is initialized so that in the initial state the data selector 14 selects and outputs the signal at the input terminal B, the comparison data DB varies as indicated in Fig. 1(F) and thus the pixel recording pulse signal S, which effects pixel recording, as indicated in Fig. 1(G), can be obtained.

Furthermore, the comparison data production circuit indicated in Fig. 4 is provided further with a counter 11 and a monostable multi-vibrator (hereinbelow abbreviated to MM) 16 (block indicated by a broken line). It is possible to vary the screen angle. When a recording operation begins, the timing treatment circuit 4 outputs a high level signal and when the operation is terminated, an printing signal PAGE is produced. The counter 11 is a 2-bit binary counter, in which, when its counting value reaches "3", the carry signal Car becomes high, and screen angle data SD are loaded, when the printing signal PAGE is low. When the carry signal Car of the counter 11 is low, the FF 12 is preset. As the result, since the data selector 14 selects and outputs the signal at the input A, the initial value of the comparison data DB is "0". To the contrary, when the carry signal Car is high, the FF 12 is cleared. As the result, since the data selector 14 selects and outputs the signal at the input B, the initial value of the comparison data DB is "15".

When the recording of one scanning line is terminated, the recording scanning signal LINE1 becomes low, the counter 11 counts up. In the case where the counting value of the counter 11 varies as "0" → "1", "1" → "2", since the carry signal Car remains low, when the recording scanning signal LINE1 is changed to the low level and the MM 16 is triggered so that a short pulse signal is produced at its output terminal $Q_{16}$, this pulse signal $Q_{16}$ is given to the clear terminal CLR of the FF 12, which is therefore cleared. In the case where the counting value of the counter 11 varies as "2" → "3", the carry signal Car is changed to the high level and thus the pulse signal $Q_{16}$ generated by the MM 16 is given to the preset terminal PR of the FF 12, which is therefore preset. Further, in the case where the counting value of the counter 11 is "3" and the carry signal Car is at the high level, since the load terminal L of the counter 11 is at the low level, the following counting value of the counter 11 is screen angle data SD. Consequently, when the screen angle data SD is "3", the FF 12 is preset and when it is not, the FF 12 is reset. This operation is continued as far as the recording is terminated and the printing signal PAGE becomes low.

Figs. 5 (H) -(P) are timing charts showing the operation of production of the pixel recording pulse signal S controlled by this circuit and the pixel recording, in which (H) and (I) represent a case where the screen angle data SD are "3", (H) showing the operation of production of the pixel recording pulse signal, (I) illustrating a pixel recording pattern by means of the pixel recording pulse signal, which is obtained as the result of the operation indicated in (I). The abscissa corresponds to the recording scanning direction, where it represents the time in (H) and the scanning position in (I), but it is indicated here by the pixel number. The ordinate corresponds to the direction, along which the recording medium is sent, in which it represents the time in (H) and the transfer amount in (I), but it is indicated here by the scanning line number. Further, for the ordinate, the counting value of the counter 11 is written together therewith. (J) and

(K) show the case where the screen angle data SD are "2"; (L) and (M) the case where the screen angle data SD are "1"; and (N) and (O) the case where the screen angle data SD are "0".

In the case where the screen angle data SD are "3", since the counting value of the counter 11 is always "3" as indicated in Fig. 5 (H) and thus the carry signal Car of the counter 11 is always at the high level, the FF 12 is preset every time the level of the recording scanning signal LINE1 becomes low. Consequently the initial value of the comparison data DB for every scanning line is "15" and the same operation of production of the pixel recording pulse signal as indicated in Fig.1(F) is repeated. As the result the pixel recording pattern for each of the scanning lines based on the pixel recording pulse signal thus obtained is such that the pixels of pixel numbers 1 and 2, and 3 and 4 are continuous, as indicated in Fig. 5(I).

In the case where the screen angle data SD are "2", since the counting value of the counter 11 varies in the order of the scanning line number "2", "3", "2", "3",..., as indicated in Fig. 5(J), the carry signal Car of the counter 11 repeats to be at the low and high levels alternately and therefore the initial value of the FF 12 for each of the scanning lines is alternately "clear", "preset", "clear", ... in the order of the scanning line number. Consequently the initial value of the comparison data DB for each of the scanning lines is "0", when the scanning line number is odd, and "15", when the scanning line number is even. As the result the same operations of production of the pixel recording pulse signal as indicated in Figs. 1 (D) and (F), respectively, are alternately repeated. Consequently, for the scanning line having an odd number, as indicated in Fig. 5(K), pixels of pixel numbers 2 and 3, 4 and 5 form pairs and their pixel recording is continuous. To the contrary, for the scanning line having an even number, the pixel recording of the pixels number 1 and 2, 3 and 4 is continuous.

In the case where the screen angle data SD are "1", the counting value of the counter 11 repeats a same pattern as "1", "2", "3", "1", "2", "3", ..., as indicated in Fig. 5(L). Consequently, since the initial value of the comparison data DB for each of the scanning lines repeats "0", "0", "15", ... in the order of the scanning line number, the pixel recording pattern is such that it is indicated in Fig. 5(M).

In the case where the screen angle data SD are "0", the counting value of the counter 11 is represented by a repetition of "0", "1", "2", "3". Consequently, since the initial value of the comparison data DB repeats "0", "0", "0", "15", ... in the order of the scanning line number, the pixel recording pattern is such that it is indicated in Fig. 5(P).

Comparing the pixel recording patterns indicated in Figs. 5 (I), (K), (M) and (P), it can be understood that the screen angle of the recording pattern varies depending on the value of the screen angle data SD. In a full color laser beam printer by multiple printing when the screen angles of different colors are identical, Moiree fringes are produced and the image quality is lowered. Consequently, in the case of such a color printing, it is possible to obtain a high quality color image without Moiree fringe by varying the value of the screen angle data SD for every color.

In the embodiment described above, increase or decrease in the number of bits in the pixel depth data DA, the comparison data DB and the screen angle data SD, modifications in the waveform of the comparison data DB, e.g. modification into a form permitting to compensate characteristics of the printer, and further modifications of the method, by which the value of the screen angle data SD is set, are freely chosen.

It is obvious that this invention can be applied not only to the laser beam printer, but also other scanning recording type printing recording devices mentioned previously.

As explained above, according to this invention, since, in a pixel recording pulse signal generation method, by which depth data DA of each of pixels in an image signal are transformed into an image recording pulse signal having a time width proportional to the depth for each of the pixels and production of recording energy is controlled so as to be interrupted by the image recording pulse signal, the recording pulse signal is so produced that the rear end of the recording pulse signal of the preceding recording side pixel in a pair of pixels adjacent to an arbitrarily selected pixel in the recording scanning direction is in accordance with the rear end of the arbitrarily selected pixel and the front end of the recording pulse signal of the succeeding recording side pixel is in accordance with the front end of the arbitrarily selected pixel, production of recording energy is continuous between the pixels of these pairs, that is, the ratio of the areas of the unstable regions stated above can be reduced so that the factor lowering the image quality produced by interruptions of the recording energy and thus lowering of the image quality are alleviated.

Figs. 3 (C) and (D) are schemes illustrating the principle of 100% UCR according to this invention.

Fig. 3(A) indicates a cross-sectional view of a structure, where yellow ink Y, magenta ink M and cyan ink C are printed in this order on a white paper sheet concentrically at a net point so that they are superposed on each other. A Δ sign in Fig. 3 indicates a boundary between two adjacent pixels. Fig. 3(B) indicates the same structure, for

which 100% UCR is effected according to the concentric solution model. As indicated in the figure, all the parts, where the three colors, yellow, magenta and cyan are superposed on each other so as to represent black points, are replaced by net points formed by black ink. Consequently, in the case where the net points (dots) of the three colors have a same size as the fourth pixel from the left, since they can be represented only by black net points (dots), there is no color shear in printing due to superposition of different colored inks and further the amount of used colored inks is relatively small.

Fig. 3(C) illustrates an example, in which 100% UCR is effected according to this invention. In this example, colored dots such as yellow, magenta, cyan, etc. are put to the left within the pixel and only black dots are put to the right. When dots are printed in this way, the black dots and colored ones are not superposed on each other by calculation of 100% UCR. Consequently there are no colored inks, which have been used in vain under a black dots in the concentric solution model and the number of colored inks superposed on each other at a dot is at most 2, what reduces transfer defectives.

Furthermore, when colored dots are put to the left side corresponding to one end of the pixel in the scanning direction for the first pixel (from the left); the black dot is put to the right side corresponding to the other end of the pixel in the scanning direction; to the contrary, for the second pixel adjacent to the first pixel, the black dot is put to the left side and the colored dots are put to the right and so forth, that is, the position of the colored dots and that of the black dot are replaced alternately for every pixel, as indicated in Fig. 3(D), dots in two pixels adjacent to each other can be put together.

When they are printed in this way, they become larger in appearance and thus the central portion of the dots can be used with a higher efficiency. Further, at the same time, in this manner, since printing becomes less sensitive to shear of different colors in printing, it is possible to realize a color reproduction with a high fidelity having no Moiré fringes.

Fig. 6 shows top views of the surface of the paper sheet for the embodiment of this invention indicated in Fig. 3(D). Fig 3(D) is reproduced at the first line of Fig. 6.

The first pixel is divided from the left of the pixel into four parts, i.e. a part printed double with cyan ink and yellow ink, a part printed only with cyan ink, a blanc part and a part printed only with black ink. Since the second pixel begins from the left by a black part, the black part of the first pixel and that of the second pixel are jointed together. On the whole it seems that black parts and colored parts are arranged alternately. When this procedure of arrangement is changed also for every line as indicated in the figure, the whole print is equivalent in appearance to a dot printing having a screen angle of 45°. The 5-th and 6-th lines in Fig. 6 illustrate a formation of dots, which is closer to the real image.

Fig. 7 is a block diagram showing the construction of a circuit, for which the embodiment of this invention indicated in Fig. 3(D) to a digital printer scanned continuously in the horizontal direction as in a television and Fig. 8 shows schemes for explaining its working mode. In Fig. 7 equivalent or identical items are represented by the same reference numerals as those used for the circuits indicated in Figs. 2 and 4.

For explaining Figs. 7 and 8 more concretely, the depth of the data DA allocated to each of the pixels of an image is represented by using e.g. a 3-bit number from "0" to "7". Consequently intermediate tones can be indicated by intermediate values among 8. An octal binary counter 13 and a pixel address counter of the frame memory 1, in which pixel data DA are stored, are cleared by the line synchronization signal LINE of a digital printer (e.g. laser beam printer, thermal head printer, ink jet printer, liquid crystal printer, semiconductor laser printer, light emitting diode printer) 77. At the same time the flip-flop (hereinbelow abbreviated to FF) 12 is set or preset depending on the phase data Car (cf. Fig.4). The counter 13 counts the reference clock CLK coming from a clock oscillator 10 so that its output increases starting from "0". When the output of the FF 12 is low, the data selector 14 outputs the output of the counter 13 as it is as the comparison data DB, and when it is high, the data selector 14 outputs the reversed value of the output of the counter 13 as the comparison data DB. Consequently, when the output of the FF 12 is low, the comparison data DB increase from "0" to "7" and when it is high, the comparison data DB decreases from "7" to "0". When the content of the counter 13 has reached "7" and returned again to "0", the most significant bit MSB of the output of the counter 13 falls. Responding thereto, the memory 1 outputs the following pixel data and at the same time the FF 12 is reversed. Since the selector 14 reverses the comparison data by the reverse of the FF 12, as the result the comparison data DB begin with "0", when the phase data FD is "low", and go and return between "0" and "7". Therefore, they are such that they are indicated in Fig. 8(A). Further, when the FD are "high", they begin with "7" and go and return between "0" and "7". Therefore, they are such that they indicated in Figs. 8 (B) and (C). On the other hand the pixel data DA outputted by the memory 1

are inputted in the comparator 5, where it is judged which are larger, the inputted pixel data DA or the comparison data DB. There are two judgement outputs of the comparator 5. One of them is "high", if DA < DB, and the other is "high", if DA > DB. Only the latter is reversed so as to be a signal representing DA ≤ DB and both the signals are inputted in a data selector 73. The most significant bit (MSB) of the pixel data DA is used as a selection signal in the selector 73, which outputs a signal, which is "high" if DA ≤ DB for the DA from "0" to "3", and if DA < DB for the DA from "4" to "7". When this signal is imputted in a printer 77, supposing that a black point is printed, if the VD is high and a white point is printed, if the VD is low, the area ratio S of the black part printed within one pixel varies as indicated in the following table and intermediate tone printing can be effected.

Table 1

INPUTTED DATA AND AREA RATIO S OF BLACK

| DA | S (%) | DA | S (%) |
|---|---|---|---|
| 0 | 0 | 4 | 62.5 |
| 1 | 12.5 | 5 | 75 |
| 2 | 25 | 6 | 87.5 |
| 3 | 37.5 | 7 | 100 |

In general, when area-modulation is effected by equally dividing the interior of a pixel into $2^n(2^n + 1)$ different modulations are possible. Since image data are usually binary data, it is preferable to allocate the image data to $2^n$ modulations. Since S = 0% and 100% are necessary, the area-modulation is adapted to the image data in the circuit according to this invention at the sacrifice of S = 50%, which is at the middle point.

Then, when the phase data manipulated for every line or for every color, as indicated in Table 2, a printing indicated in Fig. 6 can be effected.

Table 2

PHASE DATA FD

| Color \ Line | 1 | 2 | 3 | 4 | ... |
|---|---|---|---|---|---|
| Yellow | H | L | H | L | ... |
| Magenta | H | L | H | L | ... |
| Cyan | H | L | H | L | ... |
| Black | L | H | L | H | ... |

H represents the high level.

L represents the low level.

This circuit needs no memory such as pattern generator, etc. and its construction is simple and fit for high speed operation. In addition, since the number of modulations of the area modulation is $2^n$, as indicated in Table 1, it is easy to combine it with the multi-value Dither method or the multi-value depth pattern method.

Furthermore, although the position of the dots printed within a pixel has been shifted to the left or to the right (in the main scanning direction x), the same effects can be obtained, also when they are shifted in the up-and-down direction (in the auxiliary direction y) or when they are shifted both in the left-and-right and up-and-down directions (in the main scanning direction x and the auxiliary scanning direction y). An embodiment in this case will be explained below, referring to Figs. 9 to 11.

This invention can be applied to a case where a printer is used, which can control the position of dots area-modulated and printed within a pixel not only in the main scanning direction x but also in the auxiliary scanning direction y. Fig. 9 is a scheme for explaining how dots are arranged in pixels (not visible) allocated on the surface of a paper sheet. Four types of dot positions, A, B, C and D, are conceivable on the basis of assumptions of a printer. In Fig. 9, there are five sorts of pixel data, i.e. from "0" to "4", which are depth data allocated to the pixels. "0" represents "white" and "4" "black (all over)". To the contrary "1" -"3" represent half tones between them. In the type A, the dot enlarges, starting from the up and right corner in the pixel, with increasing pixel data. In the types B, C and D the dot enlarges, starting from the up and left corner, the down and left corner and the down and the right printer receives the pixel data and information on the type, which are then recorded, as indicated in Fig. 9. Fig. 10 indicates information given to the printer for every pixel, in the case where the pixel data and the information thus received are recorded in practice, and Fig. 11 illustrates the recording result. The type information indicating the dot position within the pixel is given alternately for every pixel, such as A, B, A, B, ....., for the first line, as indicated in Fig. 10, and alternately for every pixel, such as D, C, D, C, ... for the second line. Further, on and after the third line, the type information for the first line and that for the second line are given alternately and repeatedly. As the pixel data arbitrary information of "0" - "4" is allocated to each of the pixels and this figure shows an example thereof. The result obtained by recording on a paper sheet is such that it is indicated in Fig. 11, where four dots in four pixels, two adjacent pixels in the vertical direction and two adjacent pixels in the horitzontal direction, are printed, as if they were gathered together at the centre so as to be one point.

According to this embodiment, the number of dots is reduced to 1/4 without lowering the resolving power between different pixels. That is, the ratio of area of the unstable region stated above is lowered and the worsening of the image quality is alleviated.

Fig. 12 is a block diagram illustrating the construction of still another apparatus for realizing the method according to this invention. The difference from the apparatus indicated in Fig. 7 consists in that the apparatus indicated in Fig. 12 is constructed by using a look up table memory 79 and a shift register 70 contrarily to that a data selector 14 and a comparator 5 are used in the apparatus indicated in Fig. 7. The memory 79 outputs an output pattern on the basis of the pixel data DA sent by the frame memory 1 and in-pixel phase data DFD sent by the flip-flop 12. The shift register 70 transforms it with a high speed by a parallel-serial transformation to form a video signal VDS. When the look up table is defined as follows, the apparatus works in the completely same manner as the apparatus indicated in Fig. 7.

Table 3

DIGITAL VALUE (BINARY VALUE) OF PATTERN OUTPUTTED BY LOOK UP TABLE

| IN-PIXEL PHASE DATA PFD / PIXEL DATA DA | "HIGH" | "LOW" |
|---|---|---|
| 0 | 0 (00000000) | 0 (00000000) |
| 1 | 1 (00000001) | 128 (10000000) |
| 2 | 3 (00000011) | 192 (11000000) |
| 3 | 7 (00000111) | 224 (11100000) |
| 4 | 31 (00011111) | 248 (11111000) |
| 5 | 63 (00111111) | 252 (11111100) |
| 6 | 127 (01111111) | 254 (11111110) |
| 7 | 255 (11111111) | 255 (11111111) |

The look up table memory 79 used in this embodiment receives image data of 12 bits in total from the frame memories $1_{y,m}$, $1_c$ and $1_b$ storing yellow, magenta, cyan and black data, respectively, and receives also selection signals $S_0$, $S_1$ for selecting necessary video signals and in-pixel phase data PFD, which can be expanded so that an optimum in-pixel net point arrangement can be calculated. In this case, since the position of the dot in each of the pixels can be set arbitrarily, applications as indicated below are conceivable.

Net point printing expresses, in general, colors by addition color mixing and subtraction color mixing and in general, their ratio cannot be determined unequivocally, even when a same color is expressed.

For example, in the case where red having a reduced chromaticity is expressed, it can be obtained not by superposing two colors but by juxaposing them, as indicated in Fig. 14A, where magenta is put in the left half and yellow is put in the right half. However it can be obtained also by superposing the two colors, magenta and yellow, in the left half region. The former represents an addition color mixing of magenta and yellow and the latter represents a subtraction color mixing of magenta and yellow. Of course an intermediate color mixing between them can be conceived. According to the method of this invention it is possible to vary arbitrarily the ratio of these addition color mixing and subtraction color mixing. Either the subtraction color mixing or the addition color mixing can be better, depending on used inks. Therefore, by manipulating suitably this ratio of the subtraction color mixing and the addition color mixing by means of this apparatus, it is possible for inks to exhibit better their color expressivity and therefore a wide spread color display can be obtained.

As explained above, according to this invention, since the position of the dot of very color printed within a pixel can be shifted up and down or left and right, it is possible to superpose inks ideally. time inks are used more usefully and saved. Furthermore, by unifying reasonably net points (dots) of a same color, printing becomes stronger against shear, and as the result this invention has an effect that the image quality is ameliorated in the reproduction of full color images.

## Claims

1. A scanning recording type printing method, in which an image is printed by area-modulating the interior of each of pixels, which is the smallest unit region of an image, by means of ink of at least one color, comprising:

a step of bringing the ends of the pixel in predetermined directions (x, y) and the ends of a dot formed by said ink recorded within said pixel in accordance with each other; and

a step of bringing the front end of the pixel succeeding said pixel in said directions (x, y) and the front end of a dot formed by said ink recorded within said succeeding pixel in accordance with each other.

2. A scanning recording type printing method according to Claim 1, in which one of said predetermined directions is the main scanning direction (x).

3. A scanning recording type printing method according to Claim 1, in which the other of said predetermined directions is the auxiliary scanning direction (y), which is substantially perpendicular to said main scanning direction (x).

4. In a pixel recording pulse signal generation method, by which depth data (DA) of each of pixels in an image signal are transformed into an image recording pulse signal (S) having a time width proportional to the depth for each of the pixels and production of recording energy is controlled so as to be interrupted by said image recording pulse signal is so produced that the rear end of the recording pulse signal of the preceding recording side pixel in a pair of pixels adjacent to an arbitrarily selected pixel in the recording scanning direction (x, y) is in accordance with the rear end of said arbitrarily selected pixel and the front end of the recording pulse signal of the succeeding recording side pixel is in accordance with the front end of said arbitrarily selected pixel.

5. A pixel recording pulse signal generation method, by which an intermediate chrominance is printed by effecting area-modulation by means of colored inks of at least one color (C, M, Y) within a pixel, which is the smallest unit region of spatially quantized image data, comprising at least the following steps:

effecting an area-modulation by arranging a first colored ink of at least one color (C, M, Y) at a first position within a pertinent pixel, and

effecting another area-modulation by arranging a second-colored ink of at least one color (C, M, Y) at a second position within said pixel.

6. A pixel recording pulse signal generation method, according to Claim 5, wherein said first colored ink is arranged from one end within the pixel towards the center of the pixel and said second colored ink is arranged from another end within the pixel towards the center of the pixel.

7. A pixel recording pulse signal generation method, according to Claim 4, wherein said one end and said another end are one end and the other end in the main scanning direction within the pixel.

8. A pixel recording pulse signal generation method acording to Claim 5, wherein said first colored ink is constituted by a multi-layer structure consisting of yellow ink, magenta ink and cyan ink and said second colored ink is constituted by black ink.

9. A pixel recording pulse signal generation method, according to Claim 6, wherein in an arbitrarily selected pixel, said first colored ink is arranged from one end within the pixel towards the centre of the pixel and said second colored ink is arranged from another end within the pixel towards the center of the pixel, and further said second colored ink is arranged from said another end within the pixel towards the center of the pixel and said first colored ink is arranged from said one end within the pixel towards the center of the pixel.

10. A scanning recording type printing device comprising:

a memory means (1) memorizing depth data signals (DA) for one scanning line;

a means (10, 12, 13, 14, 15) including a clock generator (10) and a counter (13) and producing a comparison data signal (DB) formed by repeating an up counting operation and a down counting operation for every pixel, which is the smallest unit region of an image;

a means (5, 9) generating a pixel recording pulse signal (S), comparing said depth data (DA) with said comparison data signal (DB);

a semiconductor laser circuit (6) producing laser light, based on said inputted pixel recording signal (S);

a means (7, 8) recording an image corresponding to said pixel recording pulse signal (S) on a recording medium by sweeping said laser light; and

a timing treatment means (4) controlling the operation of said memory means (1), said comparison data production means (10, 12, 13, 14, 15), said pixel recording pulse signal production means (5, 9) and said image recording means (7, 8).

11. A scanning recording type printing device according to Claim 10, having a counter (11) and a monostable multivibrator (16); further comprising a means (11, 16) controlling the screen angle, by controlling said means (10, 12, 13, 14, 15) producing a comparison data signal (DB).

FIG. 1


PRIOR ART
(A)
1
2
3
4
5
PIXEL NUMBER
4
7
13
2
8
PIXEL DEPTH DATA
(B)
DB
DA
15
0
TIME
t1
T
t2
2T
t3
3T
t4
4T
t5
5T
(C)
X (POSITION)
(D)
DB
DA
15
0
TIME
(E)
X (POSITION)
(F)
DB
DA
15
0
TIME
(G)
X (POSITION)




FIG.2
PRIOR ART

FIG. 3




DB
Q15
LATCH
D
En
15
DATA SELECTOR
14
Y
A
B
Sel
Q12
12
CLR
CLK
F·F
PR
COUNTER
13
Q13
CLR
CLK
Car
4
PCLK3
LINE I
PAGE
TIMING TREATMENT CIRCUIT
MONOSTABLE MULTIVIBRATOR
16
Q16
CLK
CLK1
10
CLOCK GENERATOR
11 COUNTER
Car
D
CLK
L
SD

FIG. 4

FIG. 5


SCANNING LINE NUMBER COUNT
1 2 3 4
PIXEL NUMBER
DB
DA
SD=3 (H)
SD=2 (J)
SD=1 (L)
SD=0 (N)
(I)
(K)
(M)
(P)
SCREEN ANGLE
SCREEN ANGLE
SCREEN ANGLE
TIME
SCANNING POSITION

FIG.6


1 PIXEL
1st LINE
C Y
C
W
B
M
M Y
C M
C
W
B
W
C Y
Y
W
2nd LINE
BLACK DOT
COLORED DOT
3rd LINE
COLORED DOT
BLACK DOT
4th LINE
BLACK DOT
COLORED DOT
5th LINE
6th LINE
SCREEN ANGLE 45°


77
PRINTER
VD
73
SELECTOR
LINE
DA (MSB)
5
DA < DB
DA > DB
DB
SEL
12
S
FF
R
DATA SELECTOR
14
A
B
MSB
PCLK
COUNTER
CLR
DA
13
10
CLK
CLOCK
FRAME MEMORY
Car

FIG. 7

FIG. 8


CLK
LINE
PCLK
1
2
3
7
DA
DB
0
(A)
(B)
DB ≧ DA
DB > DA
DB > DA
DB ≧ DA
DB
DA
(C)
(D)
1 PIXEL
TIME

FIG. 9




FIG. 10

| LINE NUMBER | | | | | |
|---|---|---|---|---|---|
| y 1 | 1A | 2B | 3A | 4B | 2A |
| 2 | 2D | 3C | 4D | 3C | 2D |
| 3 | 2A | 1B | 0A | 1B | 0A |
| 4 | 2D | 3C | 2D | 1C | 2D |
| 5 | 3A | 2B | 1A | 0B | 1A |
| 6 | 1D | 2C | 1D | 1C | 2D |

x

FIG. 11




77
PRINTER
VDS
70
SHIFT REGISTER
S/L
CLK
PFD
8
79
MEMORY
12
S
F·F
R
13
COUNTER
CLR
CLK
10
CLOCK
1
FRAME MEMORY
Car SIGNAL

FIG. 12

FIG. 13




FIG. 14B

FIG. 14A



European Patent Office

# EUROPEAN SEARCH REPORT

Application Number

EP 86 10 4403

## DOCUMENTS CONSIDERED TO BE RELEVANT

| Category | Citation of document with indication, where appropriate, of relevant passages | Relevant to claim | CLASSIFICATION OF THE APPLICATION (Int. Cl.4) |
|---|---|---|---|
| Y | DE-A-3 338 722 (VICTOR CO. OF JAPAN)<br>* Page 13, line 8 - page 16, line 7 * | 1-4 | H 04 N 1/40<br>H 04 N 1/46 |
| Y | GB-A-2 102 240 (DAINIPPON)<br>* Page 3, line 41 - page 4, line 15 * | 1-4 | |
| X | US-A-3 230 303 (MACOVSKI)<br>* Column 5, line 69 - column 7, line 29 * | 5-7 | |
| Y<br>A | | 8,9<br>2 | |
| Y | PATENT ABSTRACTS OF JAPAN, vol. 6, no. 142 (M-146)[1020], 31st July 1982; & JP-A-57 64 565 (CANON K.K.) 19-04-1982<br>* Abstract * | 8,9 | |
| Y | US-A-4 040 094 (EVERETT)<br>* Column 8, line 53 - column 9, line 2 * | 10,11 | |
| Y | US-A-4 384 297 (OHARA)<br>* Column 2, lines 50-63 * | 10,11 | |

TECHNICAL FIELDS SEARCHED (Int. Cl.4)

H 04 N 1/00

The present search report has been drawn up for all claims

| Place of search | Date of completion of the search | Examiner |
|---|---|---|
| THE HAGUE | 10-02-1988 | DE ROECK A.F.A. |

CATEGORY OF CITED DOCUMENTS

X : particularly relevant if taken alone
Y : particularly relevant if combined with another document of the same category
A : technological background
O : non-written disclosure

T : theory or principle underlying the invention
E : earlier patent document, but published on, or after the filing date
D : document cited in the application
L : document cited for other reasons

& : member of the same patent family, corresponding

(19) Europäisches Patentamt
European Patent Office
Office européen des brevets

(11) Publication number: **0 204 094**
**A3**

(12) # EUROPEAN PATENT APPLICATION

(21) Application number: 86104403.0

(51) Int. Cl.⁴: H04N 1/40 ; H04N 1/46

(22) Date of filing: 01.04.86

(30) Priority: 30.03.85 JP 64966/85
23.08.85 JP 184274/85

(43) Date of publication of application:
10.12.86 Bulletin 86/50

(84) Designated Contracting States:
DE GB IT NL

(88) Date of deferred publication of the search report:
25.05.88 Bulletin 88/21

(71) Applicant: HITACHI, LTD.
6, Kanda Surugadai 4-chome Chiyoda-ku
Tokyo 100(JP)

(72) Inventor: Kobayashi, Shin'ya
2467 Motoyoshidacho
Mito-shi(JP)
Inventor: Anzai, Masayasu
20-8 Kanesawacho 5-chome
Hitachi-shi(JP)

(74) Representative: Strehl, Schübel-Hopf,
Groening, Schulz
Widenmayerstrasse 17 Postfach 22 03 45
D-8000 München 22(DE)

(54) **Scanning recording type printing method and apparatus for realizing the same.**

(57) A scanning recording type printing method, by which a pixel recroding pulse signal (S) is produced by comparing a comparison data signal (DB), which is formed by repeating an up counting operation and a down counting operation for every pixel, which is the smallest unit region of an image, with a depth data signal (DA) for one scanning line and the location of each of net points of at least one color printed within a pixel is controlled by the pixel recording pulse signal (S) so that worsening of the image quality in a high precision fine image printing can be reduced.

FIG. 1




EP 0 204 094 A3

# PCT

## INTERNATIONAL SEARCH REPORT

(PCT Article 18 and Rules 43 and 44)

| Applicant's or agent's file reference | FOR FURTHER ACTION | see Notification of Transmittal of International Search Report (Form PCT/ISA/220) as well as, where applicable, item 5 below. |
|---|---|---|
| 8480-PCT/GDM | | |
| International application No. | International filing date *(day/month/year)* | (Earliest) Priority Date *(day/month/year)* |
| PCT/US 02/ 08954 | 21/03/2002 | 27/03/2001 |
| Applicant | | |
| POLAROID CORPORATION | | |

This International Search Report has been prepared by this International Searching Authority and is transmitted to the applicant according to Article 18. A copy is being transmitted to the International Bureau.

This International Search Report consists of a total of 3 sheets.

[X] It is also accompanied by a copy of each prior art document cited in this report.

1. **Basis of the report**

   a. With regard to the **language**, the international search was carried out on the basis of the international application in the language in which it was filed, unless otherwise indicated under this item.

   [ ] the international search was carried out on the basis of a translation of the international application furnished to this Authority (Rule 23.1(b)).

   b. With regard to any **nucleotide and/or amino acid sequence** disclosed in the international application, the international search was carried out on the basis of the sequence listing :

   [ ] contained in the international application in written form.

   [ ] filed together with the international application in computer readable form.

   [ ] furnished subsequently to this Authority in written form.

   [ ] furnished subsequently to this Authority in computer readble form.

   [ ] the statement that the subsequently furnished written sequence listing does not go beyond the disclosure in the international application as filed has been furnished.

   [ ] the statement that the information recorded in computer readable form is identical to the written sequence listing has been furnished

2. [ ] **Certain claims were found unsearchable** (See Box I).

3. [ ] **Unity of invention is lacking** (see Box II).

4. With regard to the **title,**

   [X] the text is approved as submitted by the applicant.

   [ ] the text has been established by this Authority to read as follows:

5. With regard to the **abstract,**

   [X] the text is approved as submitted by the applicant.

   [ ] the text has been established, according to Rule 38.2(b), by this Authority as it appears in Box III. The applicant may, within one month from the date of mailing of this international search report, submit comments to this Authority.

6. The figure of the **drawings** to be published with the abstract is Figure No. 7a, 7b

   [ ] as suggested by the applicant.

   [X] because the applicant failed to suggest a figure.

   [ ] because this figure better characterizes the invention.

   [ ] None of the figures.

A. CLASSIFICATION OF SUBJECT MATTER
IPC 7 H04N1/40

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)
IPC 7 H04N

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

EPO-Internal, WPI Data

C. DOCUMENTS CONSIDERED TO BE RELEVANT

| Category ° | Citation of document, with indication, where appropriate, of the relevant passages | Relevant to claim No. |
|---|---|---|
| X | EP 0 204 094 A (HITACHI LTD)<br>10 December 1986 (1986-12-10)<br>abstract; claims 1-3; figures 1,5,8<br>column 4, line 44 - line 55<br>column 7, line 8 - line 34 | 1,19,20 |
| A | US 5 479 263 A (JACOBS TIMOTHY W ET AL)<br>26 December 1995 (1995-12-26)<br>figure 5 | 1,19,20 |
| A | US 6 128 099 A (DELABASTITA PAUL A)<br>3 October 2000 (2000-10-03) | |

☐ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

° Special categories of cited documents :

"A" document defining the general state of the art which is not considered to be of particular relevance

"E" earlier document but published on or after the international filing date

"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

"&" document member of the same patent family

| Date of the actual completion of the international search | Date of mailing of the international search report |
|---|---|
| 8 October 2002 | 15/10/2002 |

| Name and mailing address of the ISA | Authorized officer |
|---|---|
| European Patent Office, P.B. 5818 Patentlaan 2<br>NL - 2280 HV Rijswijk<br>Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,<br>Fax: (+31-70) 340-3016 | Isa, S |

1

Form PCT/ISA/210 (second sheet) (July 1992)

| Patent document cited in search report | Publication date | Patent family member(s) | Publication date |
|---|---|---|---|
| EP 0204094 A | 10-12-1986 | JP 2039356 C | 28-03-1996 |
| | | JP 5080862 B | 10-11-1993 |
| | | JP 61225971 A | 07-10-1986 |
| | | JP 6036556 B | 11-05-1994 |
| | | JP 62045282 A | 27-02-1987 |
| | | DE 3688715 D1 | 26-08-1993 |
| | | DE 3688715 T2 | 28-10-1993 |
| | | EP 0204094 A2 | 10-12-1986 |
| | | US 4926248 A | 15-05-1990 |
| US 5479263 A | 26-12-1995 | JP 7058955 A | 03-03-1995 |
| US 6128099 A | 03-10-2000 | US 5774229 A | 30-06-1998 |